

BATTERY-BOX PREMIUM LVS

- Scalable from 4 kWh to 256 kWh
- Maximum Flexibility for any Application with up to 64 Modules Connected in Parallel
- Compatible with Market Leading 1 and 3 Phase Inverters
- Cobalt Free Lithium Iron Phosphate (LFP) Battery: Maximum Safety, Life Cycle and Power
- Capable of High-Powered Emergency-Backup and Off-Grid Function
- Patented Internal Plug Design Requires No Additional Wiring
- Self-Consumption Optimization for Residential and Commercial Applications




BATTERY-BOX PREMIUM LVS

- 4 kWh Module
- Modular Design Simplifies Transport and Installation

The BYD Battery-Box Premium LVS is a lithium iron phosphate (LFP) battery pack for use with an external inverter. A single Battery-Box Premium LVS contains between 1 to 6 battery modules LVS stacked in parallel and can reach 4 to 24.0 kWh usable capacity in one tower:

- Battery-Box LVS 4.0 (4 kWh)
- Battery-Box LVS 8.0 (8 kWh)
- Battery-Box LVS 12.0 (12 kWh)
- Battery-Box LVS 16.0 (16 kWh)
- Battery-Box LVS 20.0 (20 kWh - single tower only)
- Battery-Box LVS 24.0 (24 kWh - single tower only)

Connect up to 16 Battery-Box LVS 16.0 in parallel for a maximum size of 256 kWh. Ability to scale by adding LVS modules or parallel towers of 1 to 4 modules later.




FLEXIBLE, EFFICIENT, SIMPLE



Internal Plug Connection
No Additional Wiring Required



4 - 256 kWh
Tailored Sizing for Each Application









Extend Anytime
Easily Adapts to New Requirements



High Power
Power for Every Application

TECHNICAL PARAMETERS PREMIUM LVS

						
	LVS 4.0	LVS 8.0	LVS 12.0	LVS 16.0	LVS 20.0	LVS 24.0
Battery Module	LVS (4 kWh, 51.2 V, 45 kg)					
Number of Modules	1	2	3	4	5	6
Usable Energy [1]	4 kWh	8 kWh	12 kWh	16 kWh	20 kWh	24 kWh
Max Cont. Output Current [2]	65 A	130 A	195 A	250 A	250 A	250 A
Peak Output Current [2]	90 A, 5 s	180 A, 5 s	270 A, 5 s	360 A, 5 s	360 A, 5 s	360 A, 5 s
Dimensions (H/W/D)	478 x 650 x 298 mm	711 x 650 x 298 mm	944 x 650 x 298 mm	1177 x 650 x 298 mm	1410 x 650 x 298 mm	1643 x 650 x 298 mm
Weight	64 kg	109 kg	154 kg	199 kg	244 kg	289 kg
Nominal Voltage	51.2 V					
Operating Voltage	40-57.6 V					
Operating Temperature	-10 °C to +50°C					
Battery Cell Technology	Lithium Iron Phosphate (cobalt-free)					
Communication	CAN / RS485					
Enclosure Protection Rating	IP55					
Round-Trip Efficiency	≥95%					
Scalability [3]	Max. 64 Modules in Parallel (256 kWh)				Single Tower Only	
Certification	VDE2510-50 / IEC62619 / CE / CEC / UN38.3					
Applications	ON Grid / ON Grid + Backup / OFF Grid					
Warranty [4]	10 Years					
Compatible Inverters	Refer to BYD Battery-Box Premium LVS Minimum Configuration List					
Rated DC power	3.3kW	6.7kW	10.0kW	12.8kW	12.8kW	12.8kW
Short Circuit Current	2300A					

[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at + 25 °C. System Usable Energy may vary with different inverter brands

[2] Charge derating will occur between -10 °C and +5 °C

[3] Parallel tower function only available for 1 to 4 battery modules per tower. LVS 20.0 and LVS 24.0 can only be used as a single tower.

[4] Conditions apply. Refer to BYD Battery-Box Premium Limited Warranty Letter.

