





Technical Data sonnenBatterie hybrid 9.53

	hybrid 9.53/2.5	hybrid 9.53/5	hybrid 9.53/7.5	hybrid 9.53/10	hybrid 9.53/12.5	hybrid 9.53/15
Nominal battery capacity in kWh	2.5	5.0	7.5	10.0	12.5	15.0
Depth of discharge (DoD)	90%					
Cell technology	LFP (Lithium Iron Phosphate)					
Cabinet option 1 (2.5 kWh-5.0 kWh)						
Weight in kg	58	81	-	-	-	-
Dimensions (H/W/D) in cm	88/67/23	88/67/23	-	-	-	-
Cabinet option 2 (5.0 kWh - 15.0 kWh) ¹						
Weight in kg	85	108	131	154	177	200
Dimensions (H/W/D) in cm	186/67/23	186/67/23	186/67/23	186/67/23	186/67/23	186/67/23
Max. charging/discharging power in kW	1.1	2.5	3.3	3.3	3.3	3.3
Nominal power	4.6 kW					
Input voltage PV	100- 750 VDC					
Max. input current PV	13 A					
Number of MPP-Trackers	2					
MPP voltage range	75 - 600 V					






Cabinet option 1
Battery capacity:
2.5-5.0 kWh



Cabinet option 2
Battery capacity:
5.0-15.0 kWh



Technical Data sonnenBatterie hybrid 9.53

	hybrid 9.53/2.5	hybrid 9.53/5	hybrid 9.53/7.5	hybrid 9.53/10	hybrid 9.53/12.5	hybrid 9.53/15
Power factor range	0.9 cap. – 0.9 ind.					
DC connection	Sunclix					
Max. efficiency (battery to grid)	95%					
Max. efficiency (PV to grid)	97.5%					
Max. battery efficiency	98%					
Ambient temperature range	-5 °C – +45 °C ²					
Dust & water protection	IP30					
Operating mode	single phase					
Tests and directives	SGS TÜV Saar, IEC 62040-1, IEC 62109-1, IEC 62109-2, IEC 62619, UN38.3, IEC 62133, AS/NZS 4777.2					
Battery service life	Anytime within warranty period					
Warranty	10 years ³					
Cycles	10,000 ³					

Available options

sonnenProtect - Backup and Blackstart functionality

3 Phase metering programable with LCD screen

We reserve the right to make technical changes and updates without prior notice. Specific values, performance data and other information in this data sheet, brochures and other product information, as well as illustrations and drawings in these documents, are solely illustrative and are subject to ongoing revision and modification. We do not warrant the accuracy or completeness of any information in these documents unless otherwise explicitly stated. Only the information in order confirmation documents or purchase contracts is binding.

¹ There are two cabinet versions available. By default, the large cabinet is included (Dimensions H/W/D 98/67/23). ² Derating at approx. 35°C. ³ Warranty on all parts. To learn more about our current warranty terms and conditions, please visit sonnengroup.com/terms