



## Smart DT Series (Australia)

GoodWe smart DT series inverter is typically designed for the home solar systems, covering 4KW/5KW/6KW. By adopting cutting-edge technology of photovoltaic field, it provides three phase AC output, making home system connection well balanced, safer and more convenient. The integrated two MPPTs allow two-array inputs from different roof orientations. And the combination of both RS485 and Wi-Fi communication makes the system well interactive and extremely easy to monitor.

- Maximum Efficiency up to 96.8%
- European Efficiency up to 96.7%
- MPPT Efficiency up to 99.9%
- IP65 dust-proof and water-proof
- 45°C full-load output
- Lighter than similar products
- Multiple monitoring and communication
- Up to 80 pieces can be integrated in one system

## Technical Data

	GW4000L-DT	GW5000L-DT	GW6000L-DT
<b>DC Input Data</b>			
Max. recommended PV Power [W]	5200	6500	7800
Nominal DC Power [W]	4200	5200	6200
Max. DC voltage [V]	600	600	600
MPPT voltage range [V]	200~550	200~550	200~550
Starting voltage [V]	180	180	180
Max. DC current [A]	11/11	11/11	11/11
No. of DC connectors	2	2	2
No. of MPPTs	2 (can parallel)	2 (can parallel)	2 (can parallel)
DC connector	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol
<b>AC Output Data</b>			
Normal AC power [W]	4000	5000	6000
Max. AC power [W]	4000	5000	6000
Max. AC current [A]	7	8.5	10
Normal AC output	50/60Hz; 400Vac	50/60Hz; 400Vac	50/60Hz; 400Vac
AC output range	45~55Hz/55~65Hz; 310~480Vac	45~55Hz/55~65Hz; 310~480Vac	45~55Hz/55~65Hz; 310~480Vac
THDi	<1.5%	<1.5%	<1.5%
Power factor	0.8 leading~0.8 lagging	0.8 leading~0.8 lagging	0.8 leading~0.8 lagging
Grid connection	3W/N/PE	3W/N/PE	3W/N/PE
<b>Efficiency</b>			
Max. efficiency	96.8%	96.8%	96.8%
Euro efficiency	>95.5%	>95.5%	>95.5%
MPPT adaptation efficiency	99.9%	99.9%	99.9%
<b>Protection</b>			
Residual current monitoring unit	Integrated	Integrated	Integrated
Anti-islanding protection	Integrated	Integrated	Integrated
DC switch	Integrated (optional)	Integrated (optional)	Integrated (optional)
AC over current protection	Integrated	Integrated	Integrated
Insulation monitoring	Integrated	Integrated	Integrated
<b>Certifications&amp;Standards</b>			
Grid regulation	AS4777.2/3, G83/2, EN50438	AS4777.2/3, G83/2, EN50438	AS4777.2/3, G83/2, EN50438
Safety	IEC62109-1&-2, AS3100	IEC62109-1&-2, AS3100	IEC62109-1&-2, AS3100
EMC	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3		
<b>General Data</b>			
Dimensions (WxHxD) [mm]	516*474*192	516*474*192	516*474*192
Weight [kg]	24	24	24
Mounting	Wall bracket	Wall bracket	Wall bracket
Ambient temperature range	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)
Relative humidity	0~95%	0~95%	0~95%
Max. operating altitude	4000m(> 3000m derating)	4000m(> 3000m derating)	4000m(> 3000m derating)
Protection degree	IP65	IP65	IP65
Topology	Transformerless	Transformerless	Transformerless
Night power consumption [W]	<1	<1	<1
Cooling	Natural convection	Natural convection	Natural convection
Noise emission [dB]	<30	<30	<30
Display	5.0" LCD	5.0" LCD	5.0" LCD
Communication	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi
Standard warranty [years]	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)