

Three Phase Inverters with Synergy Technology

for the 277/480V Grid

SE66.6K / SE100K



Specifically designed to work with power optimizers

- / Easy two-person installation – each unit mounted separately, equipped with cables for simple connection between units
- / Balance of System and labor reduction compared to using multiple smaller string inverters
- / Independent operation of each unit enables higher uptime and easy serviceability
- / No wasted ground area: wall/rail mounted or horizontally mounted under the modules (10° inclination)
- / Built-in module-level monitoring with Ethernet or cellular GSM
- / Fixed voltage inverter for superior efficiency (98.1%) and longer strings
- / Integrated Connection Unit with optional integrated DC Safety Switch – eliminates the need for external DC isolators
- / Built-in RS485 Surge Protection, to better withstand lightning events
- / Advanced safety features - integrated arc fault protection and rapid shutdown
- / 135% DC oversizing, enabling higher energy production

/ Three Phase Inverter with Synergy Technology for the 277/480V Grid

SE66.6K / SE100K

	SE66.6K	SE100K	
OUTPUT			
Rated AC Power Output	66600	100000	VA
Maximum AC Power Output	66600	100000	VA
AC Output Voltage — Line to Line / Line to Neutral (Nominal)	480/277		Vac
AC Output Voltage — Line to Line Range; Line to Neutral Range	432 - 528 / 249.3 - 304.7		Vac
AC Frequency	50/60 ± 5		Hz
Maximum Continuous Output Current (per Phase) @277V	80	120	A
Grids Supported — Three Phase	3 / N / PE (WYE with Neutral)		V
Maximum Residual Current Injection ⁽¹⁾	250 per unit		mA
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes		
INPUT			
Maximum DC Power (Module STC), Inverter / Unit	90000 / 45000	135000 / 45000	W
Transformer-less, Ungrounded	Yes		
Maximum Input Voltage	1000		Vdc
Nominal DC Input Voltage	850		Vdc
Maximum Input Current	2 x 40	3 x 40	Adc
Reverse-Polarity Protection	Yes		
Ground-Fault Isolation Detection	350kΩ Sensitivity per Unit ⁽²⁾		
Maximum Inverter Efficiency	98.1		%
European Weighted Efficiency	98		%
Nighttime Power Consumption	< 12		W
ADDITIONAL FEATURES			
Supported Communication Interfaces ⁽³⁾	RS485, Ethernet, GSM plug-in (optional)		
RS485 Surge Protection	Built-in		
Rapid Shutdown	Optional ⁽⁴⁾ (Automatic upon AC Grid Disconnect)		
Cable Covers	Ordered separately with part number: DCD-SGY-COVER-LP (for SE66.6K) DCD-SGY-COVER-HP (for SE100K) ; Dimensions (H x W x D) – 314.3 x 343.7 x 134.5 mm		
CONNECTION UNIT			
DC Disconnect (optional)	1000V / 2 x 40A	1000V / 3 x 40A	
STANDARD COMPLIANCE			
Safety	IEC-62109, AS3100		
Grid Connection Standards ⁽⁵⁾	VDE-AR-N-4105, G59/3, AS-4777, EN 50438 , CEI-021, VDE 0126-1-1, CEI-016, BDEW		
Emissions	IEC61000-6-2, IEC61000-6-3 , IEC61000-3-11, IEC61000-3-12		
RoHS	Yes		
INSTALLATION SPECIFICATIONS			
Number of units	2	3	
AC Output Cable	Cable gland — diameter 22-32; PE gland diameter 10-16	Cable gland — diameter 30-38; PE gland diameter 10-16	mm
DC Input ⁽⁶⁾	6 strings, 4-10mm ² DC wire, gland outer diameter 5-10mm / 3 MC4 pairs per unit	9 strings, 4-10mm ² DC wire, gland outer diameter 5-10mm / 3 MC4 pairs per unit	
AC Output Wire	Aluminum or Copper; L, N: Up to 70, PE: Up to 35	Aluminum or Copper; L, N: Up to 95, PE: Up to 50	mm ²
Dimensions (H x W x D)	Primary Unit: 940 x 315 x 260; Secondary Unit: 540 x 315 x 260		mm
Weight	Primary Unit: 48; Secondary Unit 45		kg
Operating Temperature Range	-40 to +60 ⁽⁷⁾		°C
Cooling	Fan (user replaceable)		
Noise	< 60		dB(A)
Protection Rating	IP65 — outdoor and indoor		
Mounting	Brackets provided		

(1) If an external RCD is required, its trip value must be ≥ 300mA per unit (≥ 600mA for SE66.6K; ≥ 900mA for SE100K)

(2) Where permitted by local regulations

(3) Refer to Datasheets -> Communications category on Downloads page for specifications of optional communication options: <http://www.solaredge.com/groups/support/downloads>

(4) Inverter with rapid shutdown part number: SE100K-RWRP0BNU4; Available for SE100K

(5) For all standards refer to Certifications category on Downloads page: <http://www.solaredge.com/groups/support/downloads>

(6) The DC input type, MC4 or glands, and DC switch depends on the part number ordered. Inverter with glands and DC switch P/N: SExxK-xx0P0BNG4, inverter with glands and without DC switch P/N: SExxK-xx0P0BNU4, inverter with MC4 and with DC switch P/N: SExxK-xx0P0BNU4, inverter with MC4 and without DC switch P/N: SExxK-xx0P0BNU4

(7) For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note.pdf>