

H2 SERIES

THREE PHASE



H2-5K-T2 | H2-6K-T2
H2-8K-T2 | H2-10K-T2



Easy setting of smart working modes

AFCI AFCI (optional)

15A DC 15A/ string matched with ultra high PV modules

150% 150% DC oversizing



Battery fast charging/ discharging supported

100% Supported 100% three phase voltage imbalance

UPS With UPS function switch time \leq 10ms

110% 110% AC overloading

H2-5K/ 6K/ 8K/ 10K-T2

MODEL	H2-5K-T2	H2-6K-T2	H2-8K-T2	H2-10K-T2
DC Input				
Max. PV Array Power [Wp]@STC	7500	9000	12000	15000
Max. DC Voltage [V]		1000		
MPPT Voltage Range [V]		180~900		
Rated DC Voltage [V]		600		
Start Voltage [V]		180		
Max. DC Input Current [A]		15 / 15		
Max. DC Short Circuit Current [A]		18 / 18		
No. of MPPT		2		
No. of Strings per MPPT		1/1		
Battery Parameters				
Battery Type		Lithium battery		
Battery Voltage Range [V]		180~600		
Rated Charging/ Discharging Current [A]		30/30		
Rated Charging/ Discharging Power [W]	5000	6000	8000	10000
AC Output [On-grid]				
Rated AC Power [W]	5000	6000	8000	10000
Rated Apparent Power [VA]	5500	6600	8800	11000
Rated AC Current [A]@230Vac	7.2	8.7	11.6	14.5
Max. AC Current [A]	8.3	10.0	13.3	16.7
Rated AC Voltage		220/ 380V, 230/ 400V, 3L/ N/ PE		
Rated Output Frequency [Hz]		50/ 60 ±5		
Power Factor [cos φ]		0.8 leading~0.8 lagging		
Total Harmonic Distortion [THDi]		<3%		
AC Output [Back-up Mode]				
Rated Output Power [VA]	5000	6000	8000	10000
Max. Output Current [A]	8.0	9.6	12.8	15.9
Rated Output Voltage		220/ 380V, 230/ 400V, 3L/ N/ PE		
Rated Output Frequency [Hz]		50/ 60 ±5		
Output THDv (@ Liner Load)		<3%		
Peak Output Apparent Power [VA]	10000, 60s	12000, 60s	16000, 60s	16500, 60s
Efficiency				
Max. Efficiency		98.0%		
Euro Efficiency		97.6%		
Max. Battery Charging/ Discharging Efficiency		97.6%		
Protection				
AC Short Circuit Protection		Integrated		
Overload Protection		Integrated		
Residual Current Monitoring Unit		Integrated		
Battery Input Reverse Polarity Protection		Integrated		
Anti-islanding Protection		Integrated		
AC Surge Protection		Type III		
DC Surge Protection		Type III		
AFCI		Optional		
Interface				
PV Connection		MC4		
Battery Connection		Quick connector		
AC Output		Plug-in connector		
Display		LED+APP		
Communication Port		CAN/ RS485/ DRM/ RS232		
Communication		Wi-Fi/ Ethernet/ 4G (Optional)		
General Data				
Topology		Transformerless		
Operating Temperature Range		-40°C to +60°C		
Cooling Method		Natural convection		
Ambient Humidity		0%~100% non-condensing		
Altitude		4000m (>3000m power derating)		
Noise [dBA]		<30		
Ingress Protection		IP65		
Mounting		Rear panel		
Dimensions [H*W*D] [mm]		433*549*207		
Weight [kg]		25		
Warranty [Year]		5/10/15/20/25		
Applicable Standard		CEI 0-21, VDE4105-AR-N, VDE0126-1-1, EN50438, G98, G99, EN50549, AS4777.2 IEC62109-1&-2, EN61000-6-1/2/3/4		