


MAXEON 3 SOLAR PANEL

415-430 W | Up to 22.7% Efficient



Ideal for residential applications



More Lifetime Energy

Designed to maximise energy generation through leading efficiency, enhanced performance in high temperatures, and higher energy conversion in low-light conditions like mornings, evenings and cloudy days.

Uncompromising Durability

Engineered to power through all types of weather conditions with crackresistant cells and reinforced connections that protect against fatigue and corrosion, to an electrical architecture that mitigates the impact of shade and prevents hot-spot formation.



40 Years

98.0% 0.25%

Superior Sustainability

Clean ingredients, responsible manufacturing, and lasting energy production for 40 years make SunPower Maxeon panels the most sustainable choice in solar.



The Industry's Longest Warranty

SunPower Maxeon panels are covered by a 40-year warranty¹ backed by extensive third-party testing and field data from more than 33 million panels deployed worldwide.

Product and power coverage	
Year 1 minimum warranted output	,
Maximum annual degradation	



Learn more about the SPR-MAX3-XXX sunpower.maxeon.com

MAXEON 3 POWER: 415–430 W | EFFICIENCY: Up to 22.7%

Electrical Data				
	SPR-MAX3-430	SPR-MAX3-425	SPR-MAX3-415	
Nominal Power (Pnom) ²	430 W	425 W	415 W	
Power Tolerance	+5/0%	+5/0%	+5/0%	
Panel Efficiency	22.7%	22.4%	21.9%	
Rated Voltage (Vmpp)	70.4 V	70.0 V	69.2 V	
Rated Current (Impp)	6.11 A	6.07 A	6.00 A	
Open-Circuit Voltage (Voc)	81.4 V	81.3 V	81.2 V	
Short-Circuit Current (lsc)	6.57 A	6.57 A	6.55 A	
Max. System Voltage		1000 V IEC		
Maximum Series Fuse	20 A			
Power Temp Coef.		–0.27% / °C		
Voltage Temp Coef.	−0.236% / °C			
Current Temp Coef.		0.058% / °C		

Warranties, Certifications and Compliance

IEC 62716

TUV

IEC 61215, IEC 61730

1000 V: IEC 62804

REACH SVHC-163

ISO 9001:2015, ISO 14001:2015

IEC 60068-2-68, MIL-STD-810G

IEC 61701 (maximum severity)

First solar panel labeled for ingredient

transparency and LBC-compliance.⁴ First solar panel line certified for material

health, water stewardship, material

LEED and BREEAM certifications.


reutilization, renewable energy & carbon management, and social fairness. 5

Panels can contribute additional points toward

RoHS, OHSAS 18001:2007, Recycle Scheme,

Operating Condition And Mechanical Data		
Temperature	-40°C to +85°C	
Impact Resistance	25 mm diameter hail at 23 m/s	
Solar Cells	112 Monocrystalline Maxeon Gen 3	
Tempered Glass	High-transmission tempered anti-reflective	
Junction Box	IP-68, Stäubli (MC4), 3 bypass diodes	
Weight	21.2 kg	
Max. Load ⁶	Wind: 2400 Pa, 244 kg/m² front & back Snow: 5400 Pa, 550 kg/m² front	
Frame	Class 1 black anodized (highest AAMA rating)	

1046 mm



FRAME PROFILE



A. Cable Length: 1000 mm +/-10 mm

B. LONG SIDE: 32 mm SHORT SIDE: 24 mm





Please read the safety and installation instructions. Visit www.sunpower.maxeon.com/int/PVInstallGuideIEC. Paper version can be requested through techsupport.ROW@maxeon.com.

1 40-year warranty is not available in all countries or all installations and requires registration, otherwise our 25-year warranty applies. Service availability varies by country and installation provider.

2 Standard Test Conditions (1000 W/m² irradiance, AM 1.5, 25° C). NREL calibration

Standard: SOMS current, LACCS FF and Voltage.

Standard Tests ³

Ammonia Test

Salt Spray Test

Available Listings

IFLI Declare Label

Cradle to Cradle Certified[™]

Green Building Certification

Desert Test

PID Test

Bronze

Contribution

EHS Compliance

Quality Management Certs

3 Class C fire rating per IEC 61730.

4 Maxeon DC panels first received the International Living Future Institute Declare Label in 2016.

5 Maxeon DC panels are Cradle to Cradle Cradle Certified[™] Bronze Bronze www.c2ccertified.org/products/scorecard/e-series_xseries_solar_panels_-_sunpower_corporation. Cradle to Cradle Certified[™] is a certification mark licensed by the Cradle to Cradle Products Innovation Institute.

6 Safety factor 1.5 included.

Made in Philippines (Cells) Assembled in Malaysia (Module) Specifications included in this datasheet are subject to change without notice. ©2022 Maxeon Solar Technologies. All Rights Reserved. View warranty, patent and trademark information at maxeon.com/legal.

