

HiPower Series

120-CELL HALF CUT MONOCRYSTALLINE SOLAR MODULE

370 Watt

STP370S - B60/Wnhm



Features



High power output
Compared to 158.75 mm module, the power output can increase 25 - 30 W



Suntech current sorting process
System output maximized by reducing mismatch losses up to 2% with modules sorted & packaged by amperage



Excellent weak light performance
More power output in weak light condition, such as haze, cloudy, and morning



Lower operating temperature
Lower operating temperature and temperature coefficient increases the power output



Extended load tests
Module certified to withstand front side maximum static test load (5400 Pascal) and rear side maximum static test loads (3800 Pascal) *



Withstanding harsh environment
Reliable quality leads to a better sustainability even in harsh environment like desert, farm and coastline

Certifications and standards:
IEC 61215, IEC 61730, conformity to CE



Trust Suntech to Deliver Reliable Performance Over Time


- World-class manufacturer of crystalline silicon photovoltaic modules
- Unrivaled manufacturing capacity and world-class technology
- Rigorous quality control meeting the highest international standards: ISO 9001, ISO 14001 and ISO17025
- Regular independently checked production process from international accredited institute/company
- Long-term reliability tests
- 2 × 100% EL inspection ensuring defect-free modules

Special Cell Design



The unique cell design leads to reduced electrode resistance and smaller current, thus enables higher fill factor. Meanwhile, it can reduce losses of mismatch and cell wear, and increase total reflection.

Industry-leading Warranty based on nominal power



- 98% in the first year, thereafter, for years two (2) through twenty-five (25), 0.55% maximum decrease from MODULE's nominal power output per year, ending with the 84.8% in the 25th year after the defined WARRANTY STARTING DATE.***
- 15-year product warranty
- 25-year linear performance warranty

IP68 Rated Junction Box



The Suntech IP68 rated junction box ensures an outstanding waterproof level, supports installations in all orientations and reduces stress on the cables. High reliable performance, low resistance connectors ensure maximum output for the highest energy production.

* Please refer to Suntech Standard Module Installation Manual for details. **WEEE only for EU market. *** Please refer to Suntech Product Warranty for details.
made in China & Vietnam

Electrical Characteristics

STC	STP370S - B60/Wnhm
Maximum Power at STC (Pmax)	370 W
Optimum Operating Voltage (Vmp)	34.3 V
Optimum Operating Current (Imp)	10.79 A
Open Circuit Voltage (Voc)	40.9 V
Short Circuit Current (Isc)	11.49 A
Module Efficiency	20.3%
Operating Module Temperature	-40 °C to +85 °C
Maximum System Voltage	1500 V DC (IEC)
Maximum Series Fuse Rating	20 A
Power Tolerance	0/+5 W

STC: Irradiance: 1000W/m², module temperature 25 °C, AM=1.5, tolerance of Pmax is within ±1.3%.

NMOT	STP370S - B60/Wnhm
Maximum Power at NMOT (Pmax)	278.2 W
Optimum Operating Voltage (Vmp)	32.0 V
Optimum Operating Current (Imp)	8.69 A
Open Circuit Voltage (Voc)	38.7 V
Short Circuit Current (Isc)	9.17 A

NMOT: Irradiance: 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s.

Temperature Characteristics

Nominal Module Operating Temperature (NMOT)	42 ± 2 °C
Temperature Coefficient of Pmax	-0.36%/°C
Temperature Coefficient of Voc	-0.304%/°C
Temperature Coefficient of Isc	0.050%/°C


Mechanical Characteristics

Solar Cell	Monocrystalline silicon 166 mm
No. of Cells	120 (6 × 20)
Dimensions	1756 × 1039 × 35 mm (69.1 × 40.9 × 1.4 inches)
Weight	20.3 kgs (44.8 lbs.)
Front Glass	3.2 mm (0.13 inches) tempered glass
Frame	Anodized aluminium alloy
Junction Box	IP68 rated (3 bypass diodes)
Output Cables	4.0 mm ² , Landscape: (-)1200 mm and (+)1200 mm in length or customized length
Connectors	Genuine MC4


Packing Configuration

Container	20' GP	40' HC
Pieces per pallet	31	31
Pallets per container	6	26
Pieces per container	186	806
Packaging box dimensions	1786 × 1130 × 1203 mm	
Packaging box weight	679 kg	

Information on how to install and operate this product is available in the installation instructions. All values indicated in this data sheet are subject to change without prior announcement. The specifications may vary slightly. All specifications are in accordance with standard EN 50380. Color differences of the modules relative to the figures as well as the tolerances of the modules, which do not impair their proper functioning are possible and do not constitute a deviation from the specifications.



Current-Voltage & Power-Voltage Curve (370S)



Dealer information

- 07 3505 3030
- orders@solarau.com.au
- https://solarau.com.au

Distribution & Supply Chain Solutions