

Eagle 60M 300-320 Watt

MONO PERC MODULE

Positive power tolerance of 0~+3%



KEY FEATURES



Innovative Solar Cells

Five busbar monocrystalline PERC cell technology improves module efficiency



High Efficiency

Higher module conversion efficiency (up to 19.55%) due to Passivated Emmitter Rear Contact (PERC) technology



PID Free

World's 1st PID-Free module



Low-Light Performance

Advanced glass technology improves light absorption and retention



Strength and Durability

Certified for high snow (5400Pa) and wind (2400Pa) loads



Weather Resistance

Certified for salt mist and ammonia resistance

LINEAR PERFORMANCE WARRANTY


10 Year Product Warranty • 25 Year Linear Power Warranty

- ISO9001:2008 Quality Standards
- ISO14001:2004 Environmental Standards
- OHSAS18001 Occupational Health & Safety Standards


Nomenclature:

JKM320M - 60B

Code	Backsheet
null	White
B	Black



Engineering Drawings




Packaging Configurations

(Two pallets =One stack)

30 pcs/pallet, 60pcs/stack, 840 pcs/40'HQ Container

Electrical Performance & Temperature Dependence



Mechanical Characteristics

Cell Type	Monocrystalline PERC 156×156mm (6 inch)
No. of Cells	60 (6×10)
Dimensions	1650×992×35mm (65.00×39.05×1.37 inch)
Weight	19.0kg (41.9 lbs.)
Front Glass	3.2mm, Anti-reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy (Black)
Junction Box	IP67 Rated
Output Cables	12 AWG, Length: 900mm (35.43 inch)
Fire Type	Type 1

SPECIFICATIONS

Module Type	JKM300M-60		JKM305M-60		JKM310M-60		JKM315M-60		JKM320M-60	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	300Wp	224Wp	305Wp	227Wp	310Wp	231Wp	315Wp	235Wp	320Wp	239Wp
Maximum Power Voltage (Vmp)	32.6V	30.6V	32.8V	30.8V	33.0V	31.0V	33.2V	31.2V	33.4V	31.4V
Maximum Power Current (Imp)	9.21A	7.32A	9.30A	7.40A	9.40A	7.49A	9.49A	7.56A	9.59A	7.62A
Open-circuit Voltage (Voc)	40.1V	37.0V	40.3V	37.2V	40.5V	37.4V	40.7V	37.6V	40.9V	37.8V
Short-circuit Current (Isc)	9.72A	8.01A	9.83A	8.12A	9.92A	8.20A	10.04A	8.33A	10.15A	8.44A
Module Efficiency STC (%)	18.33%		18.63%		18.94%		19.24%		19.55%	
Operating Temperature (°C)	-40°C~+85°C									
Maximum System Voltage	1000VDC (UL and IEC)									
Maximum Series Fuse Rating	20A									
Power Tolerance	0~+3%									
Temperature Coefficients of Pmax	-0.37%/°C									
Temperature Coefficients of Voc	-0.28%/°C									
Temperature Coefficients of Isc	0.048%/°C									
Nominal Operating Cell Temperature (NOCT)	45±2°C									

* STC: Irradiance 1000W/m² Cell Temperature 25°C AM=1.5

NOCT: Irradiance 800W/m² Ambient Temperature 20°C AM=1.5 Wind Speed 1m/s

* Power measurement tolerance: ± 3%

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© Jinko Solar Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.
JKM300-320M-60-A1-US