


Engineered for Performance



- Robust and flexible cell connection technology. Outstanding reliability.
- Conductive adhesive, proven in the aerospace industry.
- Redundant cell to cell connections.
- Reduced panel temperature due to unique electrical bussing.

PERFORMANCE 3 | 335 W

Residential Solar Panel

SunPower Performance Panels wrap front contact cells with 30+ years of SunPower materials and manufacturing expertise. The weakest points of Conventional Panel design are eliminated to deliver superior power, reliability, value and savings.¹



High Power

Enhanced active area and monocrystalline cells increase power and savings while designing out fragile ribbons and solder bonds on the cells.



High Performance

Up to 26% more energy in the same space over 25 years.² Outperforms Conventional Panels in partial shade thanks to unique parallel circuitry. Proprietary bussing design limits power loss, maximizing production during morning and evening shading or soiling.



Premium Aesthetics

SunPower® Performance Panels with their black frame and black backsheets blend harmoniously into your roof and add elegance to your home.




High Reliability

SunPower Performance Panels are the most deployed shingled solar panel in the world.³ Innovative cell shingling mitigates the leading reliability challenges associated with conventional front contact panels by designing out fragile ribbons and solder bonds on the cells. SunPower stands behind its panels with its industry-leading Complete Confidence Warranty. SunPower's Performance Panels are warranted to produce more than 97.5% power in the first year, then declining by 0.5% per year, ending at 85.5% power after 25 years.



25 Year Combined Warranty




PERFORMANCE 3 | 335 W Residential Solar Panel


| Electrical Data | | | | | |
|--|----------------|----------------|----------------|----------------|----------------|
| Model | SPR-P3-335-BLK | SPR-P3-330-BLK | SPR-P3-325-BLK | SPR-P3-320-BLK | SPR-P3-315-BLK |
| Nominal Power (P _{nom}) ⁴ | 335 W | 330 W | 325 W | 320 W | 315 W |
| Power Tolerance | +5/-0% | +5/-0% | +5/-0% | +5/-0% | +5/-0% |
| Efficiency | 19.9% | 19.6% | 19.3% | 19.0% | 18.7% |
| Rated Voltage (V _{mpp}) | 36.8 V | 36.4 V | 35.9 V | 35.4 V | 34.9 V |
| Rated Current (I _{mpp}) | 9.11 A | 9.07 A | 9.05 A | 9.04 A | 9.03 A |
| Open-Circuit Voltage (V _{oc}) | 44.2 V | 43.9 V | 43.6 V | 43.1 V | 42.5 V |
| Short-Circuit Current (I _{sc}) | 9.76 A | 9.72 A | 9.69 A | 9.68 A | 9.66 A |
| Maximum System Voltage | 1000 V IEC | | | | |
| Maximum Series Fuse | 18 A | | | | |
| Power Temp. Coef. | -0.36% / °C | | | | |
| Voltage Temp. Coef. | -0.29% / °C | | | | |
| Current Temp. Coef. | 0.05% / °C | | | | |

| Tests And Certifications (Pending) | |
|------------------------------------|---|
| Standard Tests ⁵ | IEC 61215, IEC 61730 |
| Quality Certs | ISO 9001:2008, ISO 14001:2004 |
| EHS Compliance | OHSAS 18001:2007, Recycling Scheme |
| Ammonia Test | IEC 62716 |
| Desert Test | MIL-STD-810G |
| Salt Spray Test | IEC 61701 (maximum severity) |
| LeTID Test ⁶ | IEC 61215 (MQT 23.1 LeTID detection) draft standard |
| PID Test | Potential-Induced Degradation free: 1000 V |
| Available Listings | TUV |

| Operating Condition And Mechanical Data | |
|---|---|
| Temperature | -40°C to +85°C |
| Impact Resistance | 25 mm diameter hail at 23 m/s |
| Solar Cells | Monocrystalline PERC |
| Tempered Glass | High-transmission tempered anti-reflective |
| Junction Box | IP-67, Stäubli (MC4), 3 bypass diodes |
| Weight | 18.1 kg |
| Max. Load | Wind: 2400 Pa, 245 kg/m ² front & back Snow: 5400 Pa, 550 kg/m ² front |
| Frame | Class 1 black anodized (highest AAMA rating) |



FRAME PROFILE



- (A) Cable Length: 1200 mm +/-15 mm
- (B) Long Side: 32 mm
Short Side: 24 mm

Read safety and installation instructions before using this product.

1 Independent Shade Study by CFV Laboratory. 2016.

2 SunPower 335 W, 19.9% efficient, compared to a Conventional Panel on same-sized arrays (280 W p-multi, 17% efficient, approx. 1.64 m²), 3% more energy per watt (based on PVSIM runs for avg US climate), 0.25%/yr slower degradation rate (Jordan, et. al. Robust PV Degradation Methodology and Application. PVSC 2018).

3 Osborne. "SunPower supplying P-Series modules to a 125 MW NextEra project." PV-Tech.org. March 2017."

4 Measured at Standard Test Conditions (STC): irradiance of 1000 W/m², AM 1.5, and cell temperature 25° C.

5 Class C fire rating per IEC 61730.

6 Fraunhofer CSP LID Sensitivity according to IEC 61215 (MQT 23.1 LeTID detection), <1% power loss.

Designed in USA, assembled in China.

See www.sunpower.com for more reference information. Specifications included in this datasheet are subject to change without notice.

©2018 SunPower Corporation. All rights reserved. SUNPOWER and the SUNPOWER logo are registered trademarks of SunPower Corporation in Europe, the U.S., and other countries as well.

☎ 1 800 786 769

SUNPOWER®

PERFORMANCE

534816 REV A / A4_AU
Publication Date: December 2019